

QUICK Quinti®



Ergonomic Task chair by Quinti collection.
It exceeds the European standards required by DL 81 and is EN1335B certified.

Base

The base is made of reinforced polyamide with steel black painted cone. [d. 600] LOOP type.

Castors

Double tread with 60mm diameter , available standard or rubberized version. Both can be self-braking or move unobstructedly. The polyamide feet are interchangeable to the castors with the same pivot of base assembling .

Elevation

All Quinti gas columns are conforming to DIN 4550 norm and exceed the 4° level.

Mechanics

Quick is created in only one version of mechanism:

M6, The Permanent Contact mechanism, made of steel, is covered with black polyurethane. it allows the adjustment in height and depth of the chair. The backrest is adjustable through a wheel.

Armrests

The chair is available both with or without fixed or adjustable armrests. They are created in order to combine the best aesthetic result with high resistance. The armrests are directly attached to the seat. [see price list]


Seat & backrest

The seat exceeds the most rigorous resistance test being made of injected polypropylene. In its inside there are two metal bars which ensure high performances. Seat and backrest, injection printed, are protected by a protection-carter

Stuffing

The standard stuffings are made of polyurethane, density 40.
It is also available the 11M certified version.

DIMENSIONS



UPHOLSTERY

CREPE'

CATEGORY 1

350 gr/mtl
100% Polyester Class 1 ,EN1021/1-2
50.000 +/- 10% Mantidal rubs

BIO-EXPO

CATEGORY 2

300 gr/mt2
100% Propitex FR bacteriostatic
Class 1UNI EN ISO 354:2003
100.000 +/- 10% Mantidal rubs

EXTREME

CATEGORY 2

350 gr/mtl
100% Xtreme FR
Class , EN 1021-1/2
100.000 +/- 10% Mantidal rubs

LASER

CATEGORY 2

560 gr/mtl
100% Polyester
FR
Class 1
80.000+/- 10% Mantidal rubs

ECO-LEATHER

CATEGORY 2

630 gr/mt2
83% PVC, 17% Syntetic
ISO 379-DIN75200-CSERF4/83 10%
Mantidal rubs

ERA

CATEGORY 3

448 gr/mtl
100% Trevira CS
Class 1UNI EN ISO 354:2003
100.000 +/- 10% Mantidal rubs

MELANGE

CATEGORIA 3

390 g/lin.m
100% Trevira CS
Class 1
80.000 +/- 10% Mantidal rubs

JET

CATEGORY 3

365+/- 5% g/lin.m
100% Polyester FR
Class 1
80.000+/- 10% Mantidal rubs

ECO-LEATHER PRO SYSTEM

CATEGORY 3

710 gr/mt2
Surface 93% PVC
Polyester Base 28%
CLASS1
100.000 rubs

LASER PLUS

CATEGORY 3

630 gr/mtl
100% Polyester FR Trevira
Class 1 , 4.000 +/- Mantidal rubs

ECO-LEATHER SOUL

CATEGORY 3

760 gr/mt2
Surface 100% POLYURETHANE,
Polyester base 85%,17% Cotton
E>100.000 EN ISO 5470-2 /1

USAGE AND MAINTENANCE

In order to have an optimal maintenance of the products and to preserve the characteristics of the materials by which they are made, it is recommended the following course of action.

FABRICS

Cleaning: check the dedicated selection written on the color Swatch card.

Usage: it is recommended to pay careful attention to the fabrics as they can be cut or ripped easily.

WOODS

Cleaning: clean using a soft cloth, soaked in tepid water. Dry always after the cleaning. Remove immediately any liquid substances or other residue in order to prevent the absorption.

Usage: wooden surfaces, being a natural material, might be subjected to color alterations with sun exposure and use over time. It is reminded that wooden surfaces cannot endure direct heat sources.

METALS

Cleaning: both steel and aluminum surfaces, and the painted ones, have to be cleaned using a soft cloth soaked in tepid water. For the most persistent stains it is possible to dilute mild soap with water moderately. Dry always after the cleaning, using a soft cloth of deer-hide. Do not use cleaning products for steel, chlorine, bleach or other strong products. It is not recommended to use abrasive, scourers, which can scratch the metal surfaces.

Usage: pay attention to the food stains as coffee, coke, fruit juices which can make indelible marks on the surfaces.

WARRANTY

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or materials supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.